

JIC: **A320-29-11-00 / 00**

Title: **CHAFING OF HYDRAULIC LINES IN THE MID PYLON AREA**

Area:

ATA: **29-11**

Special Codes: **EN**

A/C: **BIS**

Job Instruction Card for - / -

ITEM ONE - INSPECTION OF HYDRAULIC HOSE/TUBE AS
Panels: none

Zones: none

References: none

PERF. JIC A320-29-11-00, Rev. 00 HEADER - APPROVAL DATA

Prepared by: 93869; 29.08.2017

Approved by: 11700; 31.08.2017

MECH
INSP
STEP 1 - GENERAL INFORMATION
MECH
INSP

WARNING

BE CAREFUL WHEN YOU USE CONSUMABLE MATERIALS. OBEY THE MATERIAL MANUFACTURER'S INSTRUCTIONS AND YOUR LOCAL REGULATIONS.

STEP 2 - ENGINE 1 - ENGINE DATA
MECH
INSP

NOTE: INSPECTION MUST BE PERFORMED FOR DETECTING OF ANY SIGNS OF CHAFING AND PIPES FREEPLAY IN THE FIVE CLAMP BLOCKS LOCATED IN THE MID PYLON AREA

NOTE: REMOVE FOLLOWING ACCESS PANELS TO GET ACCESS INTO PYLON AREA

413AL

437AL

438AR

451AL

452AR

PERFORM OF DVI FOR CHAFING OF HYDRAULIC LINES IN MID PYLON AREA

ENG#1

IAW AMM TASK 20-23-11-200-001

DURING THE DETAILED INSPECTION, CHECK FOR ANY SIGNS OF CHAFING, THIS INCLUDES PRESENCE OF WHITE POWDER (INDICATION THAT THE TEFLON BUSH IS WEARING), PRESENCE OF GREY POWDER (INDICATION THAT THE PIPE / CLAMP IS WEARING) OR EVIDENCE OF HYDRAULIC LEAKAGE.

FINDINGS:

_____ **YES (WO** _____ **)**

_____ **NO**

PERFORM CORRECTIVE ACTIONS IF IT IS NECESSARY

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: **A320-29-11-00 / 00**

Title: **CHAFING OF HYDRAULIC LINES IN THE MID PYLON AREA**

Area:

ATA: **29-11**

Special Codes: **EN**

A/C: **BIS**

Job Instruction Card for - / -

STEP 3 - ENGINE 2 - PREPARATION
MECH
INSP

NOTE: INSPECTION MUST BE PERFORMED FOR DETECTING OF ANY SIGNS OF CHAFING AND PIPES FREEPLAY IN THE FIVE CLAMP BLOCKS LOCATED IN THE MID PYLON AREA

NOTE: REMOVE FOLLOWING ACCESS PANELS TO GET ACCESS INTO PYLON AREA

423AL

447AL

448AR

461AL

462AR

PERFORM OF DVI FOR CHAFING OF HYDRAULIC LINES IN MID PYLON AREA

ENG#2

IAW AMM TASK 20-23-11-200-001

DURING THE DETAILED INSPECTION, CHECK FOR ANY SIGNS OF CHAFING, THIS INCLUDES PRESENCE OF WHITE POWDER (INDICATION THAT THE TEFLON BUSH IS WEARING), PRESENCE OF GREY POWDER (INDICATION THAT THE PIPE / CLAMP IS WEARING) OR EVIDENCE OF HYDRAULIC LEAKAGE.

FINDINGS:

_____**YES (WO**_____)

_____**NO**_____

PERFORM CORRECTIVE ACTIONS IF IT IS NECESSARY

STEP 4 - CLOSE UP
MECH
INSP

RETURN AIRCRAFT TO SERVICEABLE CONDITION

PROPERTY OF "ROSSIYA AIRLINES" JSC