

JIC: 13467 / 0

Title: THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Area: SYS2

ATA:

Special Codes:

A/C: BIV

Job Instruction Card for - / -

ITEM 1 - THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Panels: 312AR (EMPEN AND FUSE TAIL - PANEL 1 - RIGHT SIDE)
Zones: 310 (FUSLG TAIL SECTION AFT OF AFT PRESS BHD SIDE: LR)
References: EASA AD: 2016-0184 Rev.00
 SB: 27-1227 Rev.03
Material: 19-003 LINT-FREE COTTON CLOTH 1.0 req.
 11-002 DRY CLEANING SOLVENT (VARSOL/WHITE) 0.5 req.
 04-037 GENERAL PURPOSE LITHIUM GREASE 0.3 req.

STEP 01

HEADER. APPROVAL DATA.

Prepared by: 10657 15 FEB 2017
 Approved by: 11700 16 FEB 2017

MECH	INSP

STEP 02

GENERAL INFORMATION.

WARNING

MAKE SURE THAT YOU OBEY ALL THE WARNINGS AND ALL THE CAUTIONS INCLUDED IN THE REFERENCED PROCEDURES

CAUTION

ALWAYS OBEY THE PRECAUTIONS THAT FOLLOW TO KEEP ELECTRICAL WIRING IN A SATISFACTORY CONDITION (ELECTRICALLY AND MECHANICALLY SERVICEABLE). WHEN YOU DO MAINTENANCE WORK, REPAIRS OR MODIFICATIONS, ALWAYS KEEP ELECTRICAL WIRING, COMPONENTS AND THE WORK AREA AS CLEAN AS POSSIBLE. TO DO THIS:

- PUT PROTECTION, SUCH AS PLASTIC SHEETING, CLOTHS, ETC. AS NECESSARY ON WIRING AND COMPONENTS.
- REGULARLY REMOVE ALL SHAVINGS, UNWANTED MATERIAL AND OTHER CONTAMINATION.

THESE PRECAUTIONS WILL DECREASE THE RISK OF CONTAMINATION AND DAMAGE TO THE ELECTRICAL WIRING INSTALLATION.
 IF THERE IS CONTAMINATION, REFER TO ESPM 20-55-00.

MECH	INSP

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: 13467 / 0

Title: THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Area: SYS2

ATA:

Special Codes:

A/C: BIV

Job Instruction Card for - / -

STEP 03

STANDARD PRACTICES.

1. For the Frame (FR) identification, refer to AMM 06-31-53, Page Block 001.
2. For the identification of zones, refer to AMM 06-20-00, Page Block 001.

MECH

INSP

STEP 04

Mech. Skill: B1

JOB SET-UP.

 **NOTE**

The items given in this note shall be considered as the basic Aircraft configuration before you start a maintenance task:

- Aircraft on the ground resting on landing gear (the ground safety locks and the wheel chocks are in position on the landing gear)
- Engine shut down, thrust reversers closed and locked
- Aircraft in clean configuration
- Parking brake applied
- Aircraft electrical network de-energized
- Hydraulic systems depressurized
- Access to the cockpit and cabin is available
- All circuit breakers are in closed position
- All controls in NORM, AUTO or OFF position.

1. Make sure that the aircraft is electrically grounded, refer to AMM Task 12-34-24-869-002.
2. Put an access platform in position at zone 310.
3. Do the Job Set-Up procedure as specified in the inspection of the magnetic chip detector, refer to AMM Task 27-44-51-200-002.
4. Do the Job Set-Up procedure as specified in the detailed inspection of the ballscrew and nut, refer to AMM Task 27-44-51-220-001.
5. Do the Job Set-Up procedure as specified in the detailed inspection of the upper and lower attachments, refer to AMM Task 27-44-51-220-002.

MECH

INSP

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: 13467 / 0

Title: THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Area: SYS2

ATA:

Special Codes:

A/C: BIV

Job Instruction Card for - / -

STEP 05.

Mech. Skill: B1 Dble. Rel. Skill: B1

MECH

INSP

DO A SPECIAL DETAILED INSPECTION OF THE THS ACTUATOR.

1. Do a Special Detailed Inspection of the THS Actuator.

Refer to Figure 01.

1.1. Do the inspection of the magnetic chip detector, refer to AMM Task 27-44-51-200-002.

 **NOTE**

It is not necessary to perform the boroscopic inspection of power gear detailed in AMM Task 27-44-51-200-002.

1.2. Do a detailed inspection of the ballscrew and nut, refer to AMM Task 27-44-51-220-001.

1.3. Do a detailed inspection of the upper and the lower attachments, refer to AMM Task 27-44-51-220-002.

1.3.1. In case of finding during above steps 1.1, 1.2 or 1.3 replace the THS Actuator **BEFORE THE NEXT FLIGHT** . Proceed to the Step 06 "Repair. General Information" and subsequent.

1.3.2. If no finding during above steps 1, 2 or 3 proceed to the Step 12 "Close-Up".

2. Fill in the inspection report attached to the Work Order.

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: 13467 / 0

Title: THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Area: SYS2

ATA:

Special Codes:

A/C: BIV

Job Instruction Card for - / -

STEP 06

MECH

INSP

REPAIR. GENERAL INFORMATION.

----- THIS STEP IS ONLY REQUIRED IN CASE OF FINDINGS IN STEP 05.
**MARK THIS STEP AS NOT APPLICABLE (N/A) OR NOT REQUIRED (N/R) IF YOU
 DO NOT PERFORM THIS STEP -----**

⚠ WARNING

MAKE SURE THAT YOU OBEY ALL THE WARNINGS AND ALL THE CAUTIONS
 INCLUDED IN THE REFERENCED PROCEDURES

⚠ CAUTION

ALWAYS OBEY THE PRECAUTIONS THAT FOLLOW TO KEEP ELECTRICAL WIRING IN
 A SATISFACTORY CONDITION (ELECTRICALLY AND MECHANICALLY SERVICEABLE).
 WHEN YOU DO MAINTENANCE WORK, REPAIRS OR MODIFICATIONS, ALWAYS KEEP
 ELECTRICAL WIRING, COMPONENTS AND THE WORK AREA AS CLEAN AS POSSIBLE.
 TO DO THIS:
 - PUT PROTECTION, SUCH AS PLASTIC SHEETING, CLOTHS, ETC. AS NECESSARY ON
 WIRING AND COMPONENTS.
 - REGULARLY REMOVE ALL SHAVINGS, UNWANTED MATERIAL AND OTHER
 CONTAMINATION.
 THESE PRECAUTIONS WILL DECREASE THE RISK OF CONTAMINATION AND DAMAGE
 TO THE ELECTRICAL WIRING INSTALLATION.
 IF THERE IS CONTAMINATION, REFER TO ESPM 20-55-00

STEP 07

MECH

INSP

REPAIR. STANDARD PRACTICES.

----- THIS STEP IS ONLY REQUIRED IN CASE OF FINDINGS IN STEP 05.
**MARK THIS STEP AS NOT APPLICABLE (N/A) OR NOT REQUIRED (N/R) IF YOU
 DO NOT PERFORM THIS STEP -----**

1. For the Frame (FR) identification, refer to AMM 06-31-53, Page Block 001.
2. For the identification of zones, refer to AMM 06-20-00, Page Block 001.

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: 13467 / 0

Title: THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Area: SYS2

ATA:

Special Codes:

A/C: BIV

Job Instruction Card for - / -

STEP 08.

Mech. Skill: B1	MECH	INSP
<p>REPAIR. JOB SET-UP.</p> <p>----- THIS STEP IS ONLY REQUIRED IN CASE OF FINDINGS IN STEP 05. MARK THIS STEP AS NOT APPLICABLE (N/A) OR NOT REQUIRED (N/R) IF YOU DO NOT PERFORM THIS STEP -----</p> <div style="border: 1px solid blue; padding: 10px; margin: 10px 0;"> <p style="text-align: center;">NOTE</p> <p>The items given in this note shall be considered as the basic Aircraft configuration before you start a maintenance task:</p> <ul style="list-style-type: none"> - Aircraft on the ground resting on landing gear (the ground safety locks and the wheel chocks are in position on the landing gear) - Engine shut down, thrust reversers closed and locked - Aircraft in clean configuration - Parking brake applied - Aircraft electrical network de-energized - Hydraulic systems depressurized - Access to the cockpit and cabin is available - All circuit breakers are in closed position - All controls in NORM, AUTO or OFF position. </div> <p>1. Make sure that the aircraft is electrically grounded, refer to AMM Task 12-34-24-869-002. 2. Put an access platform in position at zone 310. 3. Do the Job Set-Up procedure as specified in the removal of the THS Actuator, refer to AMM Task 27-44-51-000-001.</p>		

PROPERTY OF "ROSSIYA AIRLINES" JSC

STEP 09

Mech. Skill: B1 Dble. Rel. Skill: B1	MECH	INSP
<p>REPAIR. REPLACE THE THSA.</p> <p>----- THIS STEP IS ONLY REQUIRED IN CASE OF FINDINGS IN STEP 05. MARK THIS STEP AS NOT APPLICABLE (N/A) OR NOT REQUIRED (N/R) IF YOU DO NOT PERFORM THIS STEP -----</p> <p>1. Remove the THS Actuator. Refer to AMM Task 27-44-51-000-001. 2. Install a new THS Actuator before next flight. Refer to AMM Task 27-44-51-400-001.</p>		

JIC: 13467 / 0

Title: THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Area: SYS2

ATA:

Special Codes:

A/C: BIV

Job Instruction Card for - / -

STEP 10

Mech. Skill: B1 Dble. Rel. Skill: B1	MECH	INSP
<p>TEST AFTER REPAIR.</p> <p>----- THIS STEP IS ONLY REQUIRED IN CASE OF FINDINGS IN STEP 05. MARK THIS STEP AS NOT APPLICABLE (N/A) OR NOT REQUIRED (N/R) IF YOU DO NOT PERFORM THIS STEP -----</p> <p>Do the test procedure as specified after the installation of the THS Actuator. Refer to AMM Task 27-44-51-400-001.</p>		

STEP 11

Mech. Skill: B1	MECH	INSP
<p>CLOSE-UP AFTER REPAIR.</p> <p>----- THIS STEP IS ONLY REQUIRED IN CASE OF FINDINGS IN STEP 05. MARK THIS STEP AS NOT APPLICABLE (N/A) OR NOT REQUIRED (N/R) IF YOU DO NOT PERFORM THIS STEP -----</p> <p>1. Make sure that the work areas are clean and clear of tools and other items of equipment. 2. Do the close-up procedure as specified after the installation of the THS Actuator, refer to AMM Task 27-44-51-400-001. 3. Put the aircraft back to its initial configuration.</p>		

STEP 12.

Mech. Skill: B1	MECH	INSP
<p>CLOSE-UP.</p> <p>1. Make sure that the work areas are clean and clear of tools and other items of equipment. 2. Do the close-up procedure as specified after the inspection of the magnetic chip detector, refer to AMM Task 27-44-51-200-002. 3. Do the close-up procedure as specified after the detailed inspection of the ballscrew and nut, refer to AMM Task 27-44-51-220-001. 4. Do the close-up procedure as specified after the detailed inspection of the upper and lower attachments, refer to AMM Task 27-44-51-220-002. 5. Put the aircraft back to its initial configuration.</p>		

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: 13467 / 0

Title: THSA SPECIAL DETAILED INSPECTION. SB_CONFIG. 002.

Area: SYS2

ATA:

Special Codes:

A/C: BIV

Job Instruction Card for - / -

STEP 13.

FIGURE 01.




Figure 01.
Area to be Inspected.

N 8R 271227 K RAAA 01

MECH	INSP

PROPERTY OF "ROSSIYA AIRLINES" JSC