

JIC: **A320-32-31-02 / 00**

Title: **INSPECTION OF SENSORS MLG AND CONNECTORS**

Area:

ATA: **32-31**

Special Codes:

A/C: **BIS**

Job Instruction Card for - / -

**ITEM ONE - INSPECTION OF SENSORS MLG AND CONNECTORS**

**Panels:** none  
**Zones:** 734 (MAIN DOOR SIDE: LH), 744 (MAIN DOOR SIDE: RH)  
**References:** AMM: 24-41-00  
 AMM: 32-00-00  
 AMM: 32-12-00  
 AMM: 32-31-73  
 AMM: 32-69-00  
 ESPM: 20-48-21  
 ESPM: 20-52-12  
 ESPM: 20-52-13  
 ESPM: 20-53-51  
 ESPM: 20-55

**Material:** ARDROX AV30 RUST INHIBITOR 0.1 req.

**1-APPROVAL DATE**

PREPARED BY: 23521; 08-FEB-2018  
 APPROVED BY: 23543; 12-FEB-2018

MECH	INSP

**2-GENERAL**

 **WARNING**

PUT THE SAFETY DEVICES AND THE WARNING NOTICES IN POSITION BEFORE YOU START A TASK ON OR NEAR:

- THE FLIGHT CONTROLS
- THE FLIGHT CONTROL SURFACES
- THE LANDING GEAR AND THE RELATED DOORS
- COMPONENTS THAT MOVE.

MOVEMENT OF COMPONENTS CAN KILL OR CAUSE INJURY TO PERSONS AND/OR CAN CAUSE DAMAGE TO THE EQUIPMENT.

MECH	INSP

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: **A320-32-31-02 / 00**

Title: **INSPECTION OF SENSORS MLG AND CONNECTORS**

Area:

ATA: **32-31**

Special Codes:

A/C: **BIS**

Job Instruction Card for - / -

**3-JOB SET UP**

TOOLS AND REFERENCES.

REFERENCE	QTY	DESIGNATION
NO SPECIFIC	1	ACCESS PLATFORM 3M (10 FT)- ADJUSTABLE
NO SPECIFIC	AR	CAP - BLANKING
NO SPECIFIC	AR	SAFETY BARRIER(S)
NO SPECIFIC	AR	SAFETY CLIP - CIRCUIT BREAKER
NO SPECIFIC	AR	WARNING NOTICE(S)

MECH

INSP

**4-PREPARATION**

**A. Safety Precautions**

- (1) Put the SAFETY BARRIER(S) in position.
- (2) Install the ground safety locks on the landing gear.  
(Ref. AMM 32-00-00).
- (3) On the panel 400VU:
  - make sure that the landing-gear control-lever 6GA is in the DOWN position
  - put a WARNING NOTICE(S) in position to tell persons not to operate the landing gear.
- (4) Put a WARNING NOTICE(S) on the GRAVITY GEAR EXTN handle (panel 110VU) to tell persons not to operate the landing gear.

**B. Get Access**

- (1) Put the ACCESS PLATFORM 3M (10 FT)- ADJUSTABLE in position below the applicable zone 734 or 744.
- (2) Open the applicable MLG door  
(Ref. AMM 32-12-00).
- (3) Make sure that the GROUND LOCK SLEEVE is on the applicable MLG door actuator (Ref. AMM 32-00-00).

**C. Flight Configuration Precautions**

- (1) If the electrical power is not necessary for other maintenance tasks, de-energize the aircraft electrical circuits  
(Ref. AMM 24-41-00) .  
Then, it is not necessary to open the LGCIU circuit breakers.
- (2) If the electrical power is necessary, do the precautions for flight configuration.  
(Ref. AMM 32-00-00) before you open the LGCIU circuit breakers.

MECH

INSP

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: **A320-32-31-02 / 00**

Title: **INSPECTION OF SENSORS MLG AND CONNECTORS**

Area:

ATA: **32-31**

Special Codes:

A/C: **BIS**

Job Instruction Card for - / -

**5-OPEN CIRCUIT BREAKERS**

Open, safety and tag these circuit breakers. (AMM 32-31-73)

PANEL	DESIGNATION	FIN	LOCATION
49VU	L/G/LGCIU/SYS1/NORM	1GA	C09
121VU	HYDRAULIC/LGCIU/SYS2	2GA	Q35
121VU	HYDRAULIC/LGCIU/SYS1/GRND SPLY	52GA	Q34

EMB SB 32-1346 for A/C 001-001, 051-052, 101-110, 151-152, 201-201, 401-402, 551-552, 658-659, 708-708, 852-852, 901-901, 914-914, 930-930, 945-945

PANEL	DESIGNATION	FIN	LOCATION
121VU	LGCIU/BAT SPLY/SYS2	59GA	R33
121VU	LGCIU/BAT SPLY/SYS1	58GA	R32

MECH	INSP

**6-DETAILED VISUAL INSPECTION**

Please see work steps # 16 and # 17 pictures.

A. Disconnect the electrical connector 26GA(A), 27GA(A), 28GA(A), 29GA(A) from proximity-sensors 26GA,27GA, 28GA, 29GA.

(Ref. AMM 32-31-73)

B. Disconnect the electrical connector 20GA(A), 21GA(A), 22GA(A), 23GA(A) from proximity-sensors 20GA, 21GA, 22GA, 23GA

(Ref. AMM 32-31-73)

C. Perform connectors damage check procedure.

(Ref.ESPM 20-53-51).

1. In case of damage or corrosion presence please do step 8.

2. If there is no damage or corrosion presence please do step 7 'CLEANING OF CONNECTORS'.

(Ref.ESPM 20-55)

D. Perform DETAILED VISUAL INSPECTION MLG harness sensors and connectors.

(Ref. ESPM 20-52-12, 20-52-13).

MECH	INSP

**7-CLEANING**

PERFORM CLEANING OF CONNECTORS ACC ESPM 20-55.

MECH	INSP

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: A320-32-31-02 / 00

Title: INSPECTION OF SENSORS MLG AND CONNECTORS

Area:

ATA: 32-31

Special Codes:

A/C: BIS

Job Instruction Card for - / -

## 8-REPLACEMENT OF CONNECTORS

MECH

INSP

 **NOTE**

This step should be performed only in case of damage or corrosion presence in accordance with step 6.

PLEASE MAKE REPLACEMENT OF CONNECTORS ACC ESPM 20-48-21

 **NOTE**

A new standard of stainless steel bayonet connector ABS2426 specification is now available and fully interchangeable with EN3646 (made of Aluminum alloy) as per the IPC. Airbus recommends using this new ABS2426 standard as the preferred part number to avoid corrosion issue.

## 9-CONNECT THE ELECTRICAL CONNECTORS

MECH

INSP

Please see work steps # 16 and # 17 pictures.

Connect the electrical connectors.

A. After performing Steps 6,7,8 connect the electrical connectors:

- (1). 26GA(A), 27GA(A), 28GA(A), 29GA(A) to proximity-sensors 26GA,27GA, 28GA, 29GA
  - (2). 20GA(A), 21GA(A), 22GA(A), 23GA(A) to proximity-sensors 20GA, 21GA, 22GA, 23GA
- (Ref. AMMTASK 32-31-73)

## 10-PROTECTIVE COATING

MECH

INSP

After connected of these connectors use Dinitrol AV30 on outer surface of connected connectors for sealing. (Ref.: Airbus TFU32.00.00.007 and SIL32-078).

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: A320-32-31-02 / 00

Title: INSPECTION OF SENSORS MLG AND CONNECTORS

Area:

ATA: 32-31

Special Codes:

A/C: BIS

Job Instruction Card for - / -

**11-CLOSE CIRCUIT BREAKERS**

MECH

INSP

Remove the safety clip(s) and the tag(s) and close this(these) circuit breaker(s):

PANEL	DESIGNATION	FIN	LOCATION
49VU	L/G/LGCIU/SYS1/NORM	1GA	C09
121VU	HYDRAULIC/LGCIU/SYS2	2GA	Q35
121VU	HYDRAULIC/LGCIU/SYS1/GRND SPLY	52GA	Q34

EMB SB 32-1346 for A/C 001-001, 051-052, 101-110, 151-152, 201-201, 401-402, 551-552, 658-659, 708-708, 852-852, 901-901, 914-914, 930-930, 945-945

PANEL	DESIGNATION	FIN	LOCATION
121VU	LGCIU/BAT SPLY/SYS2	59GA	R33
121VU	LGCIU/BAT SPLY/SYS1	58GA	R32

**12-GROUND CONFIGURATION**

MECH

INSP

If you did the flight configuration precautions, put the aircraft back to the ground configuration.  
(Ref. AMM 32-00-00) .

**13-CLOSE ACCESS**

MECH

INSP

(1) Make sure that the work area is clean and clear of tools and other items.  
(2) Remove the access platform(s).  
(3) Close the MLG doors  
(Ref. AMM 32-12-00) .

**14-TEST**

MECH

INSP

Do a BITE test of the landing gear  
(Ref. AMM 32-69-00).

**15-CLOSE-UP**

MECH

INSP

Removal of Equipment (Ref. AMM 32-31-73).  
(1) Make sure that the work area is clean and clear of tools and other items.  
(2) Remove the SAFETY BARRIER(S) .  
(3) Remove the warning notice(s).  
(4) Remove the ground support and maintenance equipment, the special and standard tools and all other items.

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: A320-32-31-02 / 00

Title: INSPECTION OF SENSORS MLG AND CONNECTORS

Area:


ATA: 32-31

Special Codes:

A/C: BIS

Job Instruction Card for - / -

16-PICTURES



MECH	INSP

PROPERTY OF "ROSSIYA AIRLINES" JSC

JIC: A320-32-31-02 / 00

Title: INSPECTION OF SENSORS MLG AND CONNECTORS

Area:

ATA: 32-31

Special Codes:


A/C: BIS

Job Instruction Card for - / -

17-PICTURES

MECH

INSP



PROPERTY OF "ROSSIYA AIRLINES" JSC